



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)
BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/economy

Stanley Security Solutions Inc.

6161 East 75th Street
Indianapolis, IN 46250

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series HC2200, HC2300 & HC2800 Vertical Rod Panic Exit Devices and HC2100 Rim Exit Device w/ HCK822 Steel removable Mullion-Component Approval-Impact

APPROVAL DOCUMENT: Drawing No. "SSS002", titled "HC2100 Rim w/HCK822, Series HC2200, HC2300 & HC2800", sheets 1 through 7 of 7, prepared by Building Drops Inc., dated 06/22/11 and last revised on 11/15/12, signed and sealed by Hermes F. Norero, P.E., bearing the Miami-Dade County Product Control Renewal stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large Missile Impact Resistant

Limitations:

1. This component is approved to be used as an alternate with an approved outswing single or double Steel doors, having current NOA (Notice of Acceptance). Lowest Design Pressure of doors or the component may control.
2. See respective Design Pressure tables sheets 4-6 and limitations in sheet 1 of the component approval drawing.
3. Min thickness of 5/16" (0.3125") for HCK822 Removable mullion is required, when used with HC2300 Rim Panic
4. Electrical device installation is not part of this approval, such installation to be reviewed by AHJ.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and series and following statement: "Miami-Dade County Product Control Approved", noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA renews NOA # 12-0612.24 and consists of this page 1 and evidence pages E-1, as well as approval document mentioned above.

The submitted documentation was reviewed by Ishaq I. Chanda, P.E.



NOA No. 13-0718.03
Expiration Date: September 30, 2019
Approval Date: October 06, 2013

10/07/13

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

1. Manufacturer's die drawings and sections (Submitted under file # **12-0612.24**)
2. Drawing No. "SSS002", titled "HC2100 Rim w/HCK822, Series HC2200, HC2300 & HC2800", sheets 1 through 7 of 7, prepared by Building Drops Inc., dated 06/22/11 and last revised on 11/15/12, signed and sealed by Hermes F. Norero, P.E.

Note: This is Renewal with no change from previous approval.

B. TESTS (Submitted under files #12-0612.24 /11-0207.11 / #09-0218.09)

1. Test reports on: 1) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
2) Large Missile Impact Test per FBC, TAS 201-94
3) Cyclic Wind Pressure Loading per FBC, TAS 203-94
4) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with marked-up drawings and installation diagram of HCKR822 removable Mullion w/ HC2100 Rim Panic exit, prepared by Intertek, Test Report No. **319135MID-001**, dated 10/15/10, signed and sealed by Rick Curkeet, P. E.

2. Test reports on 1) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
2) Large Missile Impact Test per FBC, TAS 201-94
3) Cyclic Wind Pressure Loading per FBC, TAS 203-94
4) Forced Entry Test, per FBC 2411.3.2.1 and TAS 202-94

Along with installation diagrams of a Panic exit devices, prepared by Certified Testing Laboratories Architectural Division, Test Report No(s). **CTLA-1150W**, dated 02/28/04, **CTLA-1150W-1**, dated 03/18/04, **CTLA-1150W-2**, dated 03/18/04 and **CTLA-1150W-3** dated 03/19/04, signed and sealed by Ramesh Patel, P.E.

C. CALCULATIONS

1. Anchor verification calculations and structural analysis, complying with FBC 2007 & FBC 2010, prepared by Building Drops Inc., dated 06/08/12 and last revised on 11-15-2012, signed and sealed by Hermes F. Norero, P.E. (Submitted under files # **12-0612.24 /11-0207.11**)

D. QUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS


1. None.

F. STATEMENTS (except item #1, all other items below submitted under files #12-0612.24 / 11-0207.11 / #09-0218.09)

1. Statement letter of conformance FBC 2010, letter of no financial interest and renewal w/ No change, issued by Building Drops Inc., dated 05/21/13, signed and sealed by Hermes F. Norero, P.E
2. Statement letter of conformance and letter of no financial interest, Building Drops Inc., dated 06/08/12, signed and sealed by Hermes F. Norero, P.E.
3. Statement letter of Successor P.E. adopting work of another Engineer dated 11-28-12, per FL. Statue chapter 61G15-27, signed & sealed by Hermes F. Norero, P.E.
4. Certificate of Merger, issued by State of Indiana of merger of Precision Hardware Inc into surviving entity Stanley Security Solution Inc, dated May 04, 2007, signed by Todd Rokita, secretary of State.
5. Lab compliance as part of the above referenced test report.

G. OTHER

1. This NOA **renews** NOA # **12-0612.24**, expiring on SEP. 30, 2014.
2. Test proposal, dated 10/27/09, approved by BCCO.


Ishaq I. Chanda, P.E.
Product Control Examiner
NOA No. 13-0718.03
Expiration Date: September 30, 2019
Approval Date: October 17, 2013

STANLEY SECURITY SOLUTIONS, INC.
SERIES HC2200, HC2300 & HC2800 VERTICAL ROD
PANIC EXIT DEVICES AND HC2100 RIM EXIT DEVICE
WITH HCK822 STEEL REMOVABLE MULLION
(PANIC HARDWARE COMPONENT APPROVAL)

STANLEY

Security Solutions

6161 EAST 75TH STREET
INDIANAPOLIS, IN 46250
PH: (317) 806-3288
FX: (317) 806-3337

GENERAL NOTES:

1. THIS PRODUCT HAS BEEN DESIGNED AND MANUFACTURED TO COMPLY WITH THE 2010 FLORIDA BUILDING CODE INCLUDING PROVISIONS SET FORTH FOR HIGH-VELOCITY HURRICANE ZONES (HVHZ).
2. THE DOORS SHALL MEET THE FOLLOWING MINIMUM REQUIREMENTS:
- 2.1. THE DOOR SHALL BE 1-3/4" MIN. OVERALL THICKNESS
 - 2.2. DOOR PANEL SHALL BE REINFORCED WITH 22 GA. (0.029") "HAT-STIFFENERS" AT A MAXIMUM OF 6" O.C.
 - 2.3. HINGE REINFORCEMENTS AT DOOR PANEL AND AT FRAME SHALL BE A MINIMUM OF 7 GA. (0.1875") THICK STEEL.
 - 2.4. FULL-LENGTH 16 GA. (0.053" MIN.) STEEL TUBE (2 X C-NESTED CHANNELS) AT TOP & BOTTOM RAILS OF DOORS.
 - 2.5. MIN. 12 GA. (0.101" MIN.) STEEL REINFORCEMENT AT HINGE & STRIKE PLATES WHERE APPLICABLE.
 - 2.6. MIN. 14 GA. (0.067" MIN.) STEEL C-CHANNEL AT HINGE & LOCK STILES WHERE APPLICABLE.
 - 2.7. FULL LENGTH 12 GA. (0.101" MIN.) STEEL TUBE (2 X C-NESTED CHANNELS) AT STILES WHERE APPLICABLE.
 - 2.8. PLEASE REFER TO DOOR ELEVATIONS, SHEET 2, AND CORRESPONDING DETAILS FOR APPLICABILITY OF REINFORCEMENT REQUIREMENTS (SHEETS 3-7).
3. STRIKES, HINGES, AND ALL APPLICABLE REINFORCEMENTS AS REQUIRED ON DETAIL DRAWING IN THIS APPROVAL.
4. LOCKING HARDWARE SHALL BE INSTALLED AS PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.
5. ALL FASTENERS AND ASSOCIATED HARDWARE MUST BE MADE OF CORROSION RESISTANT MATERIAL OR HAVE A CORROSION RESISTANT COATING.
6. STEEL COMPONENTS SHALL BE COATED OR COMPLY WITH CORROSION RESISTANCE PROTECTION IN CONFORMANCE WITH THE MATERIAL PROTECTION PROVISIONS OF FBC SECTION 2220.
7. ALL TRIMS SHALL BE THRU BOLTED WITH #10-24 MACHINE SCREWS.
8. 1700 & 200 SERIES TRIMS AVAILABLE WITH A, B, & C STYLE PULLS.
9. 3900 & 4900 SERIES TRIMS AVAILABLE WITH A, B, C, & D LEVERS AND KNOBS.
10. OPTIONAL TRIMS MODELS INCLUDE: 1703, 2003, 4900.
11. CONFORMS TO UL10C AND UBC7-2, BHMA CERTIFIED FOR ANSI 156.3 GRADE 1.

LIMITATIONS OF USE:

1. PANIC EXIT HARDWARE DEVICES ARE APPROVED TO BE EQUAL ALTERNATIVES OF TESTED COMPONENTS TO BE USED IN 16 GA. STEEL FRAME AND 16 GA. (0.053" MIN.) STEEL SINGLE OR DOUBLE DOORS, HOLDING CURRENT NOA. THE LOWEST DESIGN PRESSURE RATING OF DOOR OR THE COMPONENT APPROVAL HEREIN SHALL CONTROL.
2. DOOR PANELS MUST NOT BE WIDER THAN 48" AND HIGHER THAN 96".
3. ELECTRICAL/ELECTRONIC FUNCTION AND INSTALLATION OTHER THAN SELF CONTAINED ELECTRONIC DEVICES ARE NOT PART OF THIS APPROVAL AND MUST BE REVIEWED BY AUTHORITY HAVING JURISDICTION(AHJ) IN THE AREA.
4. COMPLIANCE WITH BUILDING EGRESS REQUIREMENTS TO BE REVIEWED BY BUILDING OFFICIAL.

TABLE OF CONTENTS		
SHEET	REVISION	SHEET DESCRIPTION
1	-	GENERAL NOTES
2	-	DOOR ELEVATIONS
3	-	HC2100 RIM EXIT W/ HCK822 MULLION
4	-	HC2200 SURFACE VERTICAL ROD (SVR)
5	-	HC2800 CONCEALED VERTICAL ROD (CVR)
6	-	HC2800 CVR W/ HC2300 MORTISE LOCK EXIT DEVICE
7	-	BILL OF MATERIALS (BOM) & COMPONENTS

PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 13-0718-03
Expiration Date SEP 30, 2019
By [Signature]
Manufactured Product Control

TITLE: SERIES HC2200, HC2300
& HC2800 SVR AND HC2100 RIM
W/ HCK822 REMOVABLE MULL
GENERAL NOTES
PREPARED BY:
BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
PH: (954) 399-8478 FX: (954) 744-4738

REVISIONS	NO.	DESCRIPTION	BY	DATE

11.15.2012
SERIES HC2200, HC2300, & HC2800
FLORIDA BUILDING CODE
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
FBPE CERT. OF AUTHORIZATION NO. 29578





PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 12-0612-24
Expiration Date SEP 30, 2014
By [Signature]
Manufactured Product Control

DATE:	6.22.11	DWN BY:	MSS	CHK BY:	HFN	SCALE:	NTS
DWG #:		SSS002					
SHEET:		1 OF 7					

6161 EAST 75TH STREET
INDIANAPOLIS, IN 46250
PH: (317) 806-3288
FX: (317) 806-3337

TITLE: SERIES HC2200, HC2300
& HC2800 SVR AND HC2100 RIM
W/ HCK822 REMOVABLE MULL

DOOR ELEVATIONS
PREPARED BY:
BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
PH: (954) 399-8478 FX: (954) 744-4738



REVISIONS

NO.	DESCRIPTION	BY	DATE

11-15-2016
FRANCIS F. NORDEN, P.E.
FLORIDA P. E. NO. 75178
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
FPE CERT. OF AUTHORIZATION NO. 23578


PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 13-0718-03
Expiration Date 9/30/19
By: [Signature]
Product Control

PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 12-0612-24
Expiration Date SEP 30, 2019
By: [Signature]
Product Control


DATE: 6.22.11
DWN BY: MSS
CHK BY: HFN
SCALE: NTS
DWG #: SSS002
SHEET: 2 OF 7

NOTE: ALL ELEVATIONS SHOWN FROM EXTERIOR SIDE


SERIES HC2100 RIM EXIT WITH HCK 822 MULLION EXIT DEVICE		
MAX. DESIGN PRESSURE	SINGLE DOOR W/ OUT MULLION	DOUBLE DOOR WITH MULLION
POSITIVE	70 PSF	65 PSF
NEGATIVE	70 PSF	65 PSF



INTERIOR VIEW




MULLION SILL BASE




HCK 822 MULLION

NOTE: SEE SHEET 7 FOR APPLICABLE COMPONENT DETAILS



A HORIZONTAL SECTION

HC2100 RIM EXIT SINGLE DOOR APPLICATION



B HORIZONTAL SECTION

HC2100 RIM EXIT W/ HCK822 MULLION DOUBLE DOOR APPLICATION

PRODUCT RENEWED as complying with the Florida Building Code
 Acceptance No. 13-0718-03
 Expiration Date 9/30/19
 By [Signature]
 Product Control

PRODUCT REVISED as complying with the Florida Building Code
 Acceptance No. 12-0612-24
 Expiration Date 9/30/24
 By [Signature]
 Product Control

STANLEY

Security Solutions

6161 EAST 75TH STREET
 INDIANAPOLIS, IN 46250
 PH: (317) 806-3288
 FX: (317) 806-3337

TITLE: SERIES HC2200, HC2300 & HC2800 SVR AND HC2100 RIM W/ HCK822 REMOVABLE MULL

PREPARED BY: BUILDING DROPS, INC.
 398 E. DANIA BEACH BLVD. #338
 DANIA BEACH, FL 33004
 PH: (954) 999-8478 FX: (954) 744-4738

REVISIONS	NO.	DESCRIPTION	BY	DATE



HERMES F. NORCRO, P.E.
 FLORIDA P.E. NO. 73778
 398 E. DANIA BEACH BLVD. #338
 DANIA BEACH, FL 33004
 FBPP CERT. OF AUTHORIZATION NO. 29578

DATE: 6.22.11	DWN BY: MSS	CHK BY: HFN	SCALE: NTS
DWG #: SSS002			
SHEET: 3 OF 7			


SERIES HC2200 SURFACE MOUNT
VERTICAL ROD EXIT DEVICE (SVR)

MAX. DESIGN PRESSURE
(SINGLE OR DOUBLE DOORS)

POSITIVE	80 PSF
NEGATIVE	80 PSF



C HORIZONTAL SECTION
4 HC2200 SVR
SINGLE DOOR APPLICATION



D HORIZONTAL SECTION
4 HC2200 SVR
DOUBLE DOOR APPLICATION

STANLEY

Security Solutions

6161 EAST 75TH STREET
INDIANAPOLIS, IN 46250
PH: (317) 806-3288
FX: (317) 806-3337

TITLE: SERIES HC2200, HC2300
& HC2800 SVR AND HC2100 RIM
W/ HC822 REMOVABLE MULL

HC2200 SURFACE VERTICAL ROD (SVR)

PREPARED BY:

BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
PH: (954) 399-8478 FX: (954) 744-4738

REVISIONS

NO.	DESCRIPTION	BY	DATE



HERMES F. MORENO, P.E.
FLORIDA P.E. NO. 73773
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
FBBP CERT. OF AUTHORIZATION NO. 23578

PRODUCT REDESIGNED
as complying with the Florida
Building Code
Acceptance No. 13-0718-03
Expiration Date 09/30/19
By: [Signature]
Product Control


PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 12-0612-24
Expiration Date 09/30/19
By: [Signature]
Product Control

DATE: 6.22.11
DWN BY: MSS
CHK BY: HFN
SCALE: NTS
DWG #: SSS002
SHEET: 4 OF 7

SERIES HC2800 CONCEALED VERTICAL ROD EXIT DEVICE (CVR)	
MAX. DESIGN PRESSURE (SINGLE OR DOUBLE DOORS)	
POSITIVE	80 PSF
NEGATIVE	80 PSF



E5 HORIZONTAL SECTION
HC2800 CVR
SINGLE DOOR APPLICATION



F5 HORIZONTAL SECTION
HC2800 CVR
DOUBLE DOOR APPLICATION

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 13-0718-03
Expiration Date 09/30/14
By 16409 J. Chan
Product Control

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 12-0612-24
Expiration Date 09/30/14
By 16409 J. Chan
Product Control

STANLEY

Security Solutions

6161 EAST 75TH STREET
INDIANAPOLIS, IN 46250
PH: (317) 806-3288
FX: (317) 806-3337

TITLE: SERIES HC2200, HC2300 & HC2800 SVR AND HC2100 RIM W/ HC822 REMOVABLE MULL
 HC2800 CONCEALED VERTICAL ROD (CVR)


PREPARED BY:
 BUILDING DROPS, INC.
 398 E. DANIA BEACH BLVD. #338
 DANIA BEACH, FL 33004
 PH: (954) 999-8478 FX: (954) 744-4738

REVISIONS	NO.	DESCRIPTION	BY	DATE


HERNANDEZ, P.E.
 3603 E. DANIA BEACH BLVD. #338
 DANIA BEACH, FL 33004
 FBPE CERT. OF AUTHORIZATION NO. 295578

DATE: 6.22.11	DWN BY: MSS	CHK BY: HFN	SCALE: NTS
DWG #: SSS002			
SHEET: 5 OF 7			

SERIES HC2800 CVR W/ HC2300 MORTISE EXIT DEVICE	
MAX. DESIGN PRESSURE (SINGLE OR DOUBLE DOORS)	
POSITIVE	60 PSF
NEGATIVE	60 PSF




INTERIOR VIEW



G6 HORIZONTAL SECTION

HC2300 MORTISE DEVICE
SINGLE DOOR APPLICATION

NOTE: HC2300 MORTISE PANIC EXIT
MUST BE USED IN
COMBINATIONS WITH
HC2800 CVR WHEN USED IN
DOUBLE DOOR APPLICATIONS.



H6 HORIZONTAL SECTION

HC2800 CVR W/ HC2300 MORTISE DEVICE
DOUBLE DOOR APPLICATION
OR HC2800 CVR ON SINGLE OR BOTH DOOR PANELS

PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 13-0712-03
Expiration Date 09/30/19
By: [Signature]
Minut Design Products

PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 12-0612-24
Expiration Date 9/30/19
By: [Signature]
Minut Design Products

DATE: 6.22.11
DWN BY: MSS
CHK BY: HFN
SCALE: NTS
DWG #: SSS002
SHEET: 6 OF 7

REVISIONS

NO.	DESCRIPTION	BY	DATE

TITLE: SERIES HC2200, HC2300 & HC2800 SVR AND HC2100 RIM W/ HC822 REMOVABLE MULL



HC2800 CVR W/ HC2300 MORTISE

PREPARED BY:
BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
PH: (954) 399-8478 FX: (954) 744-4738

STANLEY
Security Solutions
6161 EAST 75TH STREET
INDIANAPOLIS, IN 46250
PH: (317) 806-3288
FX: (317) 806-3337

HERMES F. NORRIS, P.E.
FLORIDA P.E. NO. 7578
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
PBP CERT. NO. 29578

Item No.	QTY.	Description	Part No.	Series
1	1	3/4 THROW DEADLOCKING LATCHBOLT		HC2100
2	1	HC822 STEEL MULLIONS (ASTM-A500 STEEL GRADE B OR HIGHER STRENGTH MATERIAL) W/(4) 1/4-20 SS FLAT HEAD SCREWS		HC2100
3	1	HCK822 MULLION CAP W/(1) 1/4-20 SET SCREW & (4) 1/4-20 GR. 5 MACHINE SCREWS		HC2100
4		HCKR822 MULLION ALTERNATE CAP W(4) 1/4-20 GR. 5 MACHINE SCREWS		HC2100
5	2	MULLION FITTING ADAPTER TOP/BOTTOM		HC2100
6	1	MULLION STILL BASE W/(2) 3/8 X 2 1/4" HILTI KWIK BOLT 3 EXPANSION ANCHORS W/1 5/8" EMB. INTO CONCRETE & (1) 1/4-20 SET SCREW		HC822
7	1	INTERLOCKING ANGLE W/(1) 1/4-20 & (1) #10-24 MACHINE SCREWS S216	S216	HC2100
8	1	TOUCHBAR ASSEMBLY		HC2100, HC2200, HC2300, HC2800
9	1	DEVICE CHANNEL		HC2100, HC2200, HC2300, HC2800
10	1	HINGE FILLER		HC2100, HC2200, HC2300, HC2800
11	1	ACTIVE CASE W/(4) #10-24 MACHINE SCREWS		HC2100, HC2200, HC2300, HC2800
12	1	STRIKE W/(2) 1/4-20 & (1) 10-24 MACHINE SCREW	S300	HC2100, HC2200
13	1	TOP TOD		HC2200, HC2800
14	1	BOTTOM ROD		HC2200, HC2800
15	1	DEADLOCKING LATCHBOLT W(2) 1/4-20 MACHINE SCREWS & SEX BOLTS		HC2200
15A	1	DEADLOCKING LATCHBOLT W(2) 10-24 MACHINE SCREWS		
16	1	TOP LATCH ASSEMBLY		HC2800
17	1	BOTTOM BOLT ASSEMBLY		HC2200, HC2800
18	1	BOTTOM STRIKE W/(2) 3/8 X 2 1/4" STUD ANCHORS	S460	HC2200, HC2800
19	1	CENTER CHASSIS		HC2800
20	1	TOP STRIKE W(2) #10-24 MACHINE SCREWS	S519	HC2800
21	1	MORTISE ACTIVE CASE W(4) #10-24, (2) 1/4-20 GR. 5 MACHINE SCREWS (SINGLE DOOR ONLY)		HC2300
22	1	MORTISE CASE		HC2300
23	1	STRIKE - MORTISE CURVED LIP W/ (2) 1/4-20 SMS GR. 5		HC2300



1 HORIZONTAL SECTION

7 TYPICAL HINGE STYLE CONSTRUCTION

PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 13-0718-03
Expiration Date SEP 30, 2019
By [Signature]
Miami Dade Product Control

PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 12-0612-24
Expiration Date SEP 30, 2024
By [Signature]
Miami Dade Product Control

DATE: 6.22.11
DWN BY: MSS
CHK BY: HFN
SCALE: NTS
DWG #: SSS002
SHEET: 7 OF 7

STANLEY
Security Solutions

6161 EAST 75TH STREET
INDIANAPOLIS, IN 46250
PH: (317) 806-3288
FX: (317) 806-3337

TITLE: SERIES HC2200, HC2300
& HC2800 SVR AND HC2100 RIM
W/ HCK822 REMOVABLE MULL
BOM & COMPONENTS

PREPARED BY:
BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
PH: (954) 399-8478 FX: (954) 744-4738

REVISIONS

NO.	DESCRIPTION	BY	DATE

HERNAN F. NORCRO, P.E.
11-15-2012
398 E. DANIA BEACH BLVD. #338
DANIA BEACH, FL 33004
P.E. CERT. OF AUTHORIZATION NO. 29578